PYTHON DS

FLOOR & WALL TILE ADHESIVE

WHITE

Document No:	**DS.DOP.WHITE.v1.0**
Document Type:	Declaration of Performance
Publish Date:	27/10/2023
Product Name:	Python DS

GET A GRIP!
PYTHON ADHESIVES

DECLARATION OF PERFORMANCE IN ACCORDANCE WITH ANNEX III OF REGULATION (EU) NO. 305/2011 AS IT HAS EFFECT IN THE UNITED KINGDOM IN RESPECT OF GREAT BRITAIN (CONSTRUCTION PRODUCTS REGULATION)

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:

PYTHON S1 DS WHITE.

2. TYPE, BATCH OR SERIAL NUMBER OR OTHER IDENTIFYING MARK TO IDENTIFY THE CONSTRUCTION PRODUCT AS SET OUT IN ARTICLE 11 (4):

Product formulation reference X2040.

3. INTENDED USE AS FORESEEN BY THE MANUFACTURER OF THE CONSTRUCTION PRODUCT IN ACCORDANCE WITH DESIGNATED TECHNICAL SPECIFICATION:

Improved deformable cementitious adhesive with reduced slip and extended open time.

4. NAME, REGISTERED TRADE NAME OR REGISTERED TRADE MARK AND CONTACT ADDRESS OF THE MANUFACTURER AS SET OUT IN ARTICLE 11 (5):

Python Adhesives, Teardrop Centre, London Road, Swanley, London, BR8 8TS, United Kingdom.

5. WHEN APPLICABLE, THE NAME AND CONTACT ADDRESS OF THE AUTHORISED REPRESENTATIVE WHO HAS RECEIVED A MANDATE FOR THE TASKS SET OUT IN ARTICLE 12 (2):

Not relevant.

6. SYSTEM OR SYSTEMS FOR ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE CONSTRUCTION PRODUCT IN ACCORDANCE WITH ANNEX V:

System 3 + 4.

7. IN THE CASE OF A DECLARATION OF PERFORMANCE CONCERNING A CONSTRUCTION PRODUCT THAT IS COVERED BY A DESIGNATED STANDARD:

The approved body Ceram, No. 1289 has carried out initial type testing to System 3 and issued Test report No. (124246) - 17184.

8. IN THE CASE OF THE DECLARATION OF PERFORMANCE CONCERNING A CONSTRUCTION PRODUCT FOR WHICH A EUROPEAN TECHNICAL ASSESSMENT HAS BEEN ISSUED.

Not relevant.

9. DECLARED PERFORMANCE

ESSENTIAL CHARACTERISTICS	PERFORMANCE	HARMONISED TECHNICAL SPECIFICATION
BOND STRENGTH AS:		EN 12004:2007+A1:2012
INITIAL TENSILE ADHESION	2.1 N/mm²	
DURABILITY FOR TENSILE ADHESION:		
AFTER HEAT AGEING	1.7 N/mm²	
AFTER WATER IMMERSION	1.4 N/mm²	
AFTER FREEZE/THAW CYCLES	1.4 N/mm²	
REACTION TO FIRE	Class E WFT	
RELEASE OF DANGEROUS SUBSTANCES	See MSDS	
CLASSIFICATION - C2 TE S1		

10. DECLARATION

The performance of the product identified in items 1 and 2 in conformity with the declared performance set out in item 9. The manufacturer as defined in number 4 is solely responsible for drawing up this declaration of performance.

Signed for on behalf of the Python Adhesives by:

Ray Kingston

Ray Kingston | Technical Support Representative	DOP Number: 3033.