

Dukkaboard Fixing Washers

Product Overview

Dukkaboard Washers are engineered for secure fixing of a wide range of construction boards, providing durability, strength and stability across internal and external applications. These washers are used in conjunction with countersunk screws to fix:

- Dukkaboard OG-Panel
- Dukkaboard Shower Tray Former
- Dukkaboard CF-Panel
- Dukkaboard CN-Panel
- Dukkaboard CW-Panel

Recommended spacing is approximately 1 washer per 300mm, both horizontally and vertically.

Technical Specification – Galvanised Steel Washer

- Overall Appearance: Pressed circular washer, 35mm diameter, with punched rim and countersunk centre hole
- Material: Galvanised Steel to BS EN 10346:2009 DX51D + Z 275 M-A-C
- o Steel Thickness: 0.4mm
- o Coating Thickness: 275µm per side
- Packaging: Cardboard outer, re-closable



Technical Specifications

Product Use & Application

Washer Type	Application Areas	Suitable Use	Fixing Method	Guarantee
Stainless Steel	Universal use. Specifically for external, below ground, wall and floor applications.	External use: Below Ground, Walls, Floors	Countersunk Screw	25 Years
Galvanised Steel	Ideal for bathrooms, steam rooms, wet rooms, dry areas, walls and floors.	Internal use: Walls & Floors	Countersunk Screw	25 Years

Available Pack Sizes

Washer Type	Stock Code	Pack Size	Weight per pack
Zintec Steel	5160	100	241g
Zintex Steel	5180	1000	2500g
AISI316 Stainless-Steel	5171	100	246g

Contact and Support

For technical support or further product information, contact the Dukkaboard Knowledge Network:
www.dukkaboard.com/theknowledgenetwork

