

Document Ref:	TDS-FSBP-24H1.1
Document Type:	Technical Datasheet
Version	v.1.2
Publish Date:	03/10/2024

Flex-Seal Primer

Professional grade multi-purpose water-based acrylic primer, designed for optimal substrate preparation before applying Dukkaboard Flex-Seal Membrane in damp or high-humidity environments.



PRODUCT DESCRIPTION

Dukkaboard Flex-Seal Primer is a professional grade multi-purpose water-based acrylic primer.

Designed for optimal substrate preparation before applying Dukkaboard Flex-Seal Membrane in damp or high humidity environments.

It acts as a waterproof primer, flexible additive, and bonding agent and is ideal for reducing and regulating absorption in highly porous surfaces.

Stabilizes surface consistency and suppresses dust for better performance.

PRODUCT FEATURES

- Suitable for use on heated substrates
- Solvent Free
- Binds dust and reduces water absorption
- Low VOC emissions

PRODUCT CERTIFICATES & STANDARDS

Conforms to the requirements for NHBC Standards 2023 Clause 9.2.5 - Appropriate substrates for tiling in domestic bath and shower enclosures, wet rooms and bathroom pods.



Document Ref:	TDS-FSBP-24H1.1
---------------	-----------------

PRODUCT SPECIFICATION

	VALUE
Product Description	Dukkaboard Aqua77 Flex-Seal Primer
Liquid Basis	Styrene-butadiene
Colour	Milky Blue
Application Temperature	+5°C to +25°C
Density	1g/cm ³
pH	9
Consumption	100 - 250g/m ²

PRODUCT FORMATS AVAILABLE

STOCK CODE	SIZE (KG)	EAN 13 CODE
5481	1	N/A
5482	5	N/A

INSTRUCTIONS FOR USE

- Ensure the substrate areas are clean and dry.
- Remove all dust, dirt, oil, grease and other contaminants that may affect bonding.
- Stir well before use.
- Apply Dukkaboard Flex-Seal Primer to the substrate using a brush or roller.
- Once dry, additional coats or covering layers may be applied.
- Tools and soiled areas should be cleaned immediately after use with water.

STORAGE INSTRUCTIONS

Dukkaboard Flex-Seal Primer can be used for a period of at least 12 months when stored in its original container, in a cool and dry place.

HEALTH AND SAFETY INFORMATION

Dukkaboard Flex-Seal Primer is not hazardous according to the Ordinance on Hazardous Substances.
May be disposed of as building site waste once cured.