

Dukkaboard Aqua77 Fleece Waterproofing Kit – 6 sqm

Product Description

The Dukkaboard Aqua77 Waterproofing Kit is a complete waterproofing system designed for up to 6sqm coverage of wet-room and bathroom substrate protection prior to tiling.

It provides a seamless waterproofing layer for board joints, corners, penetrations, and mechanical fixings, ensuring a fully tanked, tile-ready surface. The system uses Dukkaboard Neo-Flex liquid-applied membrane in combination with Aqua77 Fleece+ reinforcing tape.



Item code: 5498
SSM = 1 kit bucket

Key Features

This kit is designed for:

- Waterproofing wet areas such as showers, bathrooms, wet rooms, and utility spaces.
- Sealing board-to-board joints, internal corners, and around mechanical fixings on Dukkaboard construction boards.
- Preparing substrates for ceramic, porcelain, or natural stone tiling.

Coverage: Up to 6 sqm (5 sqm of walls and 1 sqm of floor) depending on complexity and detailing.

Contents

Component	Quantity / Size	Description
Neo-Flex	5kg	Flexible liquid waterproofing membrane
Pro-Tile Primer	1Kg	Surface primer for enhanced adhesion
Fleece +Roll	10cm x 25m	Reinforcement fleece for joints
Fleece + Section	1 piece	Pre-cut fleece sheet for detail areas
Internal Corner	1 piece	Preformed internal corner sealing fleece
Paint Brush	1	For application of Neo-Flex

Application Properties

Membrane Type: liquid-applied, single component, air-curing

Reinforced with: Aqua77 Fleece+ tape (included)

Drying Time: Fast-drying

Suitability: Interior use, wet areas


Substrates: Dukkaboard boards, cement boards, suitable mineral surfaces

For full step-by-step installation, refer to the Aqua77 Tanking Kit Installation Guide document ref. IG-DNFW-23L1

Physical Packaging Details

The kit is supplied in a single plastic reusable, recyclable, and recycled bucket.

Lid Type: Tamper Evident.
Package Weight: $\pm 5\%$



Dimensions ($\pm 1\text{mm}$)	
D1	323mm
D2	311mm
D3	284mm
H (without lid)	262mm

Storage and Handling

Storage Temperature: $+5^{\circ}\text{C}$ to $+25^{\circ}\text{C}$

Keep sealed until use.

Avoid frost and direct sunlight.

Shelf life: 12 months in unopened container (following manufacturer's guidance is recommended).

Health & Safety

Use gloves and eye protection when handling liquid membrane.

Ensure adequate ventilation.

Refer to MSDS covering Neo-Flex and MSDS covering Aqua77 Primer for full safety details.

Associated products

Additional products can also be ordered separately to complement this kit:

- Neo-Flex, in 5kg and 10kg
- Primer, in 1kg and 5kg
- Fleece+ matting (1 × 10m roll)
- Corners, pipe seals,

Always consult a professional.



Contact your Dukkaboard representative for technical advice and pricing.

www.dukkaboard.com

020 8778 9000