

# DURAEELITE MAX DECOUPLING MATTING

 **TRIMLINE**



**3**  
LAYER  
BUILDUP

**9113**

**1 x 30m**

## ENGINEERED TO HANDLE MULTI-DIRECTIONAL SUBSTRATE MOVEMENT

### PRODUCT DESCRIPTION

A robust, lightweight one-step decoupling mat specifically engineered for floor tiling where substrate movement is a concern. Featuring an integrated mesh backing for enhanced stability and bonding strength, it's ideal for timber floors and cracked concrete bases.

### PRODUCT FEATURES

- Allows tiling directly over old, damaged floors
- Compatible with slightly damp mineral subfloors
- Built-in air channels promote moisture evaporation, ideal for anhydrite screeds
- Fast, efficient installation with minimal adhesive consumption
- Dimpled profile reduces adhesive use without compromising performance
- Suitable for use with standard flexible tile adhesives
- Reinforced mesh backing improves tensile strength and bond integrity
- Fully compatible with underfloor heating systems
- Resistant to chemicals, mould, rot, and bacteria

### PRODUCT TECHNICAL PROPERTIES

#### MATERIAL

Polypropylene & Polyethylene

#### MAT THICKNESS

3.6mm

#### ROLL WIDTH

1m

#### ROLL LENGTH

30m

#### TEMPERATURE RESISTANCE

-40°C to +80 °C

#### WEIGHT

700g/sqm

#### TENSILE STRENGTH

667N/622N

## DESIGNED FOR FAST AND EFFICIENT INSTALLATION

DATASHEET NUMBER: TDS-9113-V1.1 ISSUE DATE: SEPTEMBER 2025